

CLAIMS

What Is Claimed Is:

1. An optical scanning apparatus for optically scanning a surface to be scanned at a constant velocity, the optical scanning apparatus comprising:

 a light source for emitting a light flux;

 a first optical lens system for coupling the light flux emitted by the light source to a following optical lens system;

 a second optical lens system for forming the light flux from the first optical lens system into a line image extending in a direction corresponding to a main scanning direction of the surface to be scanned which is perpendicular to a sub scanning direction;

 an optical deflector for deflecting the light flux formed as the line image via a deflecting reflective plane thereof, which is located near where the line image is formed; and

 a third optical lens system for condensing the deflected light flux as an optical beam spot on the surface to be scanned; wherein

 the second optical lens system includes a glass lens and at least one plastic lens having a non-arc shape,

new
wherein the at least one plastic lens has a negative power
in the sub scanning direction.

2. A method of manufacturing an optical scanning apparatus, the method comprising the steps of:

Sub
at
optical
lens
new
providing a light source for emitting a light flux;
arranging a first optical lens system so as to couple the light flux emitted by the light source to a following optical lens system;

20270202
forming a second optical lens system to include a glass lens and at least one plastic lens having a non-arc shape and negative power in a sub scanning direction;

arranging the second optical lens system following the first optical lens system such that the second optical lens system forms the light flux from the first optical lens system into a line image extending in a direction corresponding to a main scanning direction of the surface to be scanned which is perpendicular to the sub scanning direction;

arranging an optical deflector so as to deflect the light flux formed as the line image via a deflecting reflective plane thereof, which is located near where the line image is formed; and

✓ arranging a third optical lens system so as to condense the deflected light flux as an optical beam spot on the surface to be scanned.

Sub
Alt
Emx
15-2222-011202

3. An optical scanning apparatus for optically scanning a surface to be scanned at a constant velocity, the optical scanning apparatus comprising:

means for emitting a light flux;
means for coupling the light flux emitted by said means for emitting a light flux to a means for forming the light flux into a line image;

means for forming the light flux received from the means for coupling the light flux into a line image extending in a direction corresponding to a main scanning direction of the surface to be scanned which is perpendicular to a sub scanning direction;

means for deflecting the light flux formed as the line image via a deflecting reflective plane thereof, which is located near where the line image is formed; and

means for condensing the deflected light flux as an optical beam spot on the surface to be scanned; wherein the means for forming the light flux into the line image includes a glass lens and at least one plastic lens

new
having a non-arc shape and negative power in the sub
scanning direction.

4. An image forming apparatus for forming an image by optically scanning a surface to be scanned at a constant velocity, the image forming apparatus comprising:

Sub
means for emitting a light flux;
means for coupling the light flux emitted by said means for emitting a light flux to a means for forming the light flux into a line image;
means for forming the light flux received from the means for coupling the light flux into a line image extending in a direction corresponding to a main scanning direction of the surface to be scanned which is perpendicular to a sub scanning direction;

means for deflecting the light flux formed as the line image via a deflecting reflective plane thereof, which is located near where the line image is formed; and
means for condensing the deflected light flux as an optical beam spot on the surface to be scanned; wherein

the means for forming the light flux into the line image includes a glass lens and at least one plastic lens having a non-arc shape and negative power in the sub scanning direction.